

Report

Hamilton St Gore – Civil Design Features Report for Resource Consent

Prepared for Kāinga Ora

18 May 2023



QUALITY ASSURANCE STATEMENT

TASK	NAME	SIGNATURE
Project Manager	Wayne Blanchfield	
Prepared by	Michael Tam	
Reviewed by	Brendan Hurring	
Approved for Issue by	Wayne Blanchfield	

DOCUMENT CONTROL

ISSUE	DATE	ISSUE DETAILS	AUTHOR	CHECKED	APPROVED
1	18.05.2023	For resource consent	MT	BH	WB

713093.001 29 Hamilton St Gore - Civil Design Features Report RC.

COMMERCIAL IN CONFIDENCE

This document including any intellectual property is confidential and proprietary to Calibre and may not be disclosed in whole or in part to any third party nor used in any manner whatsoever other than for the purposes expressly consented to by Calibre in writing. Calibre reserves all legal rights and remedies in relation to any infringement of its rights in respect of its confidential information | © Calibre Group Pty Ltd.

Contents

1. Introduction	3
2. Property Details	3
3. Site Location and Description	3
4. Design Standards	4
5. Earthworks	4
5.1 Earthworks	4
5.2 Erosion and Sediment Control	4
6. Rooding	4
7. Stormwater	5
7.1 Flood Hazard and Finished Floor Level	5
7.2 Existing Stormwater Reticulation	6
7.3 Proposed Stormwater	6
8. Wastewater	8
9. Water Supply	8
10. Accessibility	8

Figures

Figure 1: Site location	3
Figure 2: WSP flood analysis 1 in 100-year water levels	6

Appendices

Appendix A	Civil Design Plans
Appendix B	Stormwater Calculations
Appendix C	WSP Capacity Confirmation Email
Appendix D	Floor Level and Attenuation Correspondence

1. Introduction

Calibre Consulting Limited have been engaged by Southbase Construction Ltd to provide civil design services for a proposed 24 Lot residential development at 29 Hamilton Street in Gore, for Kāinga Ora (KO) – Homes and Communities.

This Design Feature Report (DFR) has been prepared to support the application for Resource Consent demonstrating that the roading and servicing for the site can be adequately provided. It also records design criteria, and key discussions with Council and outcomes related to the civil design for this project. It outlines catchments, modelling assumptions, council requirements, design standards and considerations undertaken for this development.

2. Property Details

Property Address:	29 Hamilton St, 11 Oxford St, East Gore, Gore
Legal Description:	Lot 9 & 10 DP 1219 and Lot 3 DP 391234
Record of Title ID:	366119
Parcel Area:	810m ² , 810m ² & 6,073m ² (7,683m ² Total)
Registered owner:	Housing New Zealand Limited
Zoning:	Gore District Plan: <ul style="list-style-type: none">• Residential A Zone (Planning Map GOR 04)• Maitara River Floodplain (Hazards and Utilities GOR 04)

3. Site Location and Description

The site is the former Longford Tavern and Function Centre located in East Gore off Hamilton St. It is shown in red on **Figure 1** below. The site is comprised in one Record of Title with a total area of 7,683m² but is made up of 3 parcels.



Figure 1: Site location

Pre-development, the site contained one large commercial building, the tavern and functional centre, with a basement underneath. The site has large car park and a Right of Way (RoW) abutting the southern boundary providing access to 13C Oxford Street. The remainder of the site (approximately 2,175m²) comprises grass and gardens and is mostly located near the eastern end of the site.

The site can be described as generally flat however it has approximately 1m of fall with the highest area adjacent to the eastern boundary and the lowest area at the western boundary adjacent to Hamilton Street.

A pre-development site survey was undertaken by Terramark Ltd in February 2023. The levels taken are in terms of NZVD 2016. A copy of the site survey (drawing numbers 230032/1A 230032/2) is attached in the drawing set with this report.

Demolition works to facilitate the proposed 24-unit residential development have commenced.

4. Design Standards

The applicable design standards were utilised in the civil design of the proposed development;

- **New Zealand Building Code** (D1-Access Routes / E1-Surface Water / E2-External Moisture / G13-Foul Water Drainage)
- **Gore District Council** (Subdivision and Land Development Bylaw 2019)
- **New Zealand Transport Agency** (Traffic Control Devices manual / Manual of traffic signs and markings).
- **NZS 4404 2010** – Land Development and Subdivision Infrastructure

5. Earthworks

The proposed site levels and cut and fill depths are shown on plans 713093.001-C200 and C201.

5.1 Earthworks

The site will be earthworked to create building platforms and to grade the site appropriately for access and drainage. The proposed site levels are shown on plan 713093.001-C200.

Cut and fill depths and volumes have been calculated by comparison of the pre-development surface and the finished ground surface. The maximum total depth of cut and fill are 0.8m and 1.3m, respectively. Total cut and fill across the site are 647m³ and 1,318m³ respectively. This indicates a net volume of 671m³ of material will be required to be imported during earthworks to achieve the finished surface levels. Additional earthworks are expected to include but not limited to excavating and backfilling of trenches for sewer, stormwater, water, other services relating to the site and the demolition and of the existing buildings.

The earthworks volumes provided above are approximate only and are subject to change in detailed design, depending on the final scheme layout and final finished ground levels. The volumes given are however a good approximation of the total volume required.

5.2 Erosion and Sediment Control

Erosion and sediment control for the site will be designed as part of the detailed civil engineering design as requirements may be altered by the final design. This will be carried out in accordance with GDC Subdivision and Land Development Bylaw 2019 (Bylaw). For this size of site these will primarily consist of creating a stabilised entranceway, silt fences and protecting adjacent sumps with sediment filtering soaks and filter fabric under the grates.

6. Roading

The proposed road layout and typical cross sections are shown on plans 713093.001-C300, C305 and C310.

The existing vehicle access to the site is from a vehicle crossing at the Hamilton Street road frontage, adjacent to the south west corner of the site. There is a second access to the site from Oxford Street. This second access is a right of

way over part of Lot 2 DP 539188 (13 Oxford Street). Lot 2 DP 550052 (13C Hamilton Street) also uses this existing RoW and also has a RoW over Lot 2 DP 539188 and part of the subject site to gain access to that lot. These existing rights of way will remain in place following the development of the site.

A new cul-de-sac (Road 1) will be constructed intersecting with Hamilton Street. Road 1 will grade upwards from Hamilton Street to the cul-de-sac head. This cul-de-sac will have a total road reserve of 11metres and a carriageway width of 6 metres. Footpaths will be constructed on both sides of the road. The cul-de-sac will have a turning head with a radius of 9.5metres. This cul-de-sac will provide access to most of the lots and will be vested in Council to become legal road.

The proposed vested road will form an intersection with Hamilton Street. This intersection will be to a road that is below arterial class, therefore is required to have a kerb radii of 9.0m as per GDC Bylaw 2019 section 3.3.7. New pedestrian cutdowns will be provided at the intersection to provide existing footpath continuation. Tactile pavers will be provided at the pedestrian cutdowns.

Lots 1 and 24 will gain access directly from Hamilton Street via new crossings to be formed on that road. The access for Lot 1 is located adjacent to the northwest corner of the site. Lot 24 access is adjacent to the southwest corner of the site and will replace the existing crossing that is in this location. Lots 2 to 15, 22 and 23 will gain legal and physical access from Road 1. The remaining 6 Lots (Lots 16 to 21) are proposed to access via RoW 1, the RoW from Oxford Street. These lots will however all also have pedestrian access from Road 1.

The portion of the right of way from Oxford Street to where it bends to the west is an existing right of way with a varying legal width of 10.65m to 11.0m because the two side boundaries of the RoW are not parallel. This portion of the RoW has a formed carriageway to a nominal width of 5.8m and has a raised nib kerb on one side. The remaining width of the RoW cross section is landscaped. This part of the right of way rises up from Oxford Street. There is no existing drainage for this portion of the right of way. No change will be made to this portion of the right of way except for providing a sump at the roadside end of the RoW that will be connected to the adjacent stormwater main. The pavement make up will be checked during construction to confirm materials and depth. As it has been used for access to the former land use it is expected that the pavement will be sufficient for the proposed land use and no upgrade would be required.

The portion of the RoW that is within the subject lot and runs adjacent to the will be 7.5m wide. This will consist of a 6.0m wide carriageway and 1.5m wide footpath. It will slope downwards towards west from the bend. The turning area and footpath that connects through to Road 1 will allow for overland flow in events that exceed the capacity of the piped system.

7. Stormwater

7.1 Flood Hazard and Finished Floor Level

The Gore District Plan shows the area of the subdivision to be within the Maitai River Floodplain. Environmental Southland (ES) has also advised that there are flood risks associated with the site as the site is situated within a basin formed by the stopbank to the west, natural high ground to the north and south and the road formation on Railway Esplanade to the southeast. This generally aligns with what is currently shown by the LIDAR contours available on the GDC GIS system.

ES has also noted the existing stopbank was designed to provide 100-year event flood protection for the area. However, the February 2020 flood event showed that the existing stopbank system through Gore and Maitai was near the maximum capacity of the flood banks. From that event ES has estimated the existing stopbank system only provides flood protection for approximately the 70-year event with updated data considered. ES has advised the existing stopbank is being assessed and is planned to be upgraded to provide a 100-year flood protection.

The designs for the subdivision have therefore not taken into account the possibility of the stop bank capacity being exceeded and the flood level is therefore calculated by assessment of the 100-year event rainfall intensity, the existing piped network and topography of the area.

Flood hazard analysis has been carried out by WSP New Zealand Ltd (WSP) on behalf of GDC for the subject site for the 1 in 100-year rainfall event. This has shown that the western extent of the site will be subject to some inundation in this rainfall event. Figure 2 below is the flood level model produced by WSP that shows 1 in 100-year water levels surrounding the site.




Figure 2: WSP water levels for the 1 in 100-year rainfall event

The levels shown on the above are in terms of Dunedin-Bluff vertical datum. The site survey and civil engineering designs have been carried out in terms of New Zealand Vertical Datum 2016 (NZVD) as this is the datum referred to in the Council Bylaw. These levels need to be reduced by 0.24m to bring them into terms of NZVD. The flood level at the Hamilton Street frontage is therefore RL 72.87.

There will continue to be some inundation of the site following the completion of the development and finished floor levels will be set in accordance with this flood level and the required 0.6m freeboard stated in the bylaw.

7.2 Existing Stormwater Reticulation

There is an existing 450 diameter stormwater main in Hamilton Street. The existing reticulation that drained the building roof water and carpark runoff connects to this main adjacent to the southeast corner of the site. The main drains to the south along Hamilton St then Oxford St and under the stop bank before discharging to the Matura River.

WSP New Zealand Ltd (WSP) infrastructure capacity assessment shows that the existing reticulation in Hamilton Street has some above ground level surcharging in the 1 in 5 year (20% AEP) events.

The secondary flow path from the site is to Hamilton Street at the west of the site.

7.3 Proposed Stormwater

The proposed stormwater design is shown on plan 713093.001-C401.

To re-develop the site to a 24-unit residential housing development, stormwater design including primary and secondary systems, stormwater management and mitigation have been considered.

7.3.1 Primary System

The primary stormwater system for the proposed development is a gravity piped system connecting to the existing reticulation in Hamilton Street. It includes piped lot connections, road sumps, manholes and stormwater mains. It is sized to accommodate the 10-minute duration, 20% AEP storm event with the rainfall data used being the climate adjusted rainfall intensity of RCP8.5 for the period 2081-2100 HIRDS online data obtained from NIWA.

GDC has noted that there are stormwater capacity issues within their existing network. However, the proposed development will have a reduced impervious area, and attenuation will be provided. The total runoff post development will therefore be less than predevelopment as there will be less impervious surfaces and more gardens and greenspace post development. As runoff from the site will be reduced there is no negative effect on the existing network from the development. Pre and post-development flow calculations are provided in Appendix B of this report.

7.3.2 Secondary System

When the capacity of the piped network is exceeded or becomes blocked the secondary flow path for stormwater runoff will be along the Right of Way 1 and Road 1 towards Hamilton Street. Flow direction arrows are shown on drawing C401 show the direction of overland flow in these events. The secondary flow path is designed to cope with 1% AEP design storms without flooding adjacent properties except for those properties that are below the expected 1 in 100-year flood level. Those properties will continue to be flooded.

Once these flow reach Hamilton Street they will continue to flow through the existing route identified on the WSP flood analysis through private property to Oxford Street and beyond.

7.3.3 Stormwater Management and Mitigation

Typically, stormwater attenuation is required to mitigate the effects of increased runoff from a new development. To establish the allowable discharge rate and attenuation a comparison between the pre- and post-development runoff is carried out. The post development allowable flow rate is set to the predevelopment flow rate and the required attenuation volume is calculated accordingly. For this development these calculations were carried out and these showed a decrease in flow from predevelopment to post development due to the net decrease in impermeable surfaces. Calculations are attached in Appendix B of this report.

GDC has noted that the critical stormwater event for their network is 5-year 60-minute storm. The attached calculations show that the post-development runoff for this event is 20.1l/s compared to the pre-development runoff of 21.5l/s. There is therefore a net decrease the stormwater runoff generated from the site.

Bylaw section 4.2.4 requires all new residential buildings to provide a minimum capacity of 3,000 litres rainwater storage tank. GDC representative Matt Bayliss has clarified that even though the new development does not intend to reuse rainwater, a capacity of 3,000-litre tank still has to be provided for each new building for the purpose of stormwater attenuation. As such, there have been discussions with GDC about the necessity of the attenuation tanks. A dispensation application of the rainwater tanks was submitted to GDC as no attenuation should be required because the development causes a net decrease in stormwater runoff. The dispensation application was however declined. There has been further correspondence with GDC and it has been accepted that the required total attenuation volume would be the total runoff generated from the proposed roof areas for the critical event. Table 1 in Appendix D records the key discussions and outcomes with respect to the stormwater management and mitigation for the proposed development.

Two attenuation options have been proposed for the development. One option is to have individual rainwater tanks for each building based on each individual roof area. The other option is to attenuate stormwater using oversized pipes located within the road system that have a restricted outlet. The oversized pipes would have a low flow pipe connecting into the GDC network restricting outflow. The oversized pipes provide the required storage volume generated by the 5-year 60-minute storm. An overflow pipe will allow flows in excess of the required storage. The oversized pipe option is the option that is preferred and has been shown on the design plans. This design will be progressed through detailed design for Engineering Approval and Building Consent.

The treatment requirements have also been discussed with GDC and it has been accepted that a proprietary system such as a Stormwater360 Stormfilter, Stormwater360 Cascade Separator, Hynds Downstream Defender or First Defence High Capacity System could be used. The treatment devices listed are able to either treat the first 25mm of rainfall or 5mm/hr of rainfall intensity of the hardstand areas in the proposed vested Road and RoW. Final design will be discussed further with Council and final details will be provided at the time of seeking Engineering Approval for the detailed design.

8. Wastewater

The proposed wastewater system is shown on plan 713093.001-C

A preliminary assessment of the GDC wastewater network capacity around the proposed development has been completed by WSP. As with the stormwater, the assessment shows that there are overflow issues in the 20% AEP stormwater events due to stormwater infiltration to the wastewater system. However, those issues are observed in the base model without the proposed development. The assessment also stated that the proposed development creates an increase in the flow within the wastewater network but the increase is not significant.

The wastewater system comprises a single DN150 main located approximately on the centreline of Road 1. All Lots have individual DN100 laterals connecting to this main. The wastewater system has been designed in accordance with Table 5.3, 5.4 and 5.5 of the GDC Bylaw 2019.

See Appendix, WSP and GDC Email.

9. Water Supply

The proposed water reticulation plan is shown on plan 7130093.001 C450.

The preliminary infrastructure assessment completed by WSP for the proposed water supply for the development shows that the proposed development will cause 0.2m drop in pressure in the network. GDC has confirmed this would be acceptable.

The water reticulation system for the proposed development mainly consists of a DN100 PVC watermain and an OD63 PE sub-main. These pipes will connection to the existing DN100 cast iron water main on the western side of Hamilton Street. The new DN100 water main will run along the northern side of Road 1 and will terminate at the cul-de-sac head with a fire hydrant. The OD63 sub-main will carry on from the fire hydrant and loop around the cul-de-sac head and link back to the existing watermain in Hamilton St on the southern side of the road.

The fire hydrant proposed provides sufficient site coverage to meet the requirements in accordance with New Zealand Fire Service Fire Fighting Water Supplies Code of Practice (SNZ PAS4509:2008).

See Appendix C, WSP Capacity Confirmation email.

10. Accessibility

Units 15-21 of the proposed development are Full Universal Design (FUD). This means that the unit must comply with all of the standards and guidelines pertaining to accessibility. The main limitations associated with accessibility come in the form of maximum gradients and crossfalls of the pavement areas. Detailed Design will confirm if the FUD units can be provided.

Appendix A Civil Design Plans

KĀINGA ORA – HOMES AND COMMUNITIES




PACKAGE GORE 29 HAMILTON STREET EAST GORE, GORE



DRAWING INDEX	
SHEET NUMBER	SHEET TITLE
C000	COVER SHEET
230032/1A	TOPOGRAPHICAL SURVEY (BY OTHERS)
230032/2	TOPOGRAPHICAL SURVEY (BY OTHERS)
C200	FINISHED GROUND CONTOURS PLAN
C201	CUT AND FILL DEPTH CONTOURS PLAN
C300	PAVEMENT PLAN
C305	ROAD LONGSECTION
C310	ROAD TYPICAL SECTIONS
C400	COMBINED SERVICES PLAN
C401	STORMWATER PLAN
C450	WASTEWATER PLAN
C500	WATER SUPPLY PLAN

Advisory
 Surveying
 Urban Development
 Infrastructure Buildings
 Structural Engineering
 Civil Engineering



- Notes:**
- Horizontal Datum: North Taieri 2000
 - Height Datum: NZVD2016
 - Origin of Levels: LP 1 DP 12637 (F2D6) - Reduced Level: 72.28m
 - Contour interval is:
Major - 0.5m
Minor - 0.1m
 - Areas and dimensions are subject to verification upon survey.
 - Easements, covenants and other legal instruments relating to this site may not be represented on this plan. A full investigation of legal records should be undertaken to confirm.
 - Not all public & private drainage information has been shown on the plan.
 - The position and alignment of services shown on this plan may have been obtained from Council records and are subject to the errors or omission of that data, they should not be used for design purposes. All services should be located on site before any design work is undertaken.
 - Critical levels are to be checked and confirmed prior to design and construction.
 - The contours shown on this plan have been electronically calculated between the survey fixed positions and may not represent the true ground levels.
 - The size and positions of any trees shown on this plan is approximate and tree types should be confirmed by an arborist if critical.
 - These notes are an integral part of the plan.

Legend:


FEATURE	DESCRIPTION
X	Spot Height
○	Tree
○	Foul Sewer Manhole
○	Stormwater Manhole
□	Mudtank
□	Water Manifold
□	Fire Hydrant
□	Power Pole
□	Electricity Pillar
□	Light Pole
—	Edge of Seal Drive
—	Edge of Seal Road
—	Kerb
—	Footpath
—	Centre Line
—	Garden
—	Hedge
—	Building
—	Top of Wall
—	Bottom of Wall
—	Contour Major
—	Contour Minor
—	Boundary
—	Abbuttals
—	Easement Boundary
—	Existing Stormwater
—	Existing Foul Sewer
—	Existing Water

DISCLAIMER:
 THE CONCEPTS AND INFORMATION CONTAINED IN THIS DRAWING ARE THE COPYRIGHT OF TERRAMARK LTD. USE OR COPYING OF THIS DRAWING IN WHOLE OR PART WITHOUT WRITTEN PERMISSION OF TERRAMARK LTD CONSTITUTES AN INFRINGEMENT OF COPYRIGHT. TERRAMARK ACCEPTS NO LIABILITY OR RESPONSIBILITY WHATSOEVER FOR, OR IN RESPECT OF, ANY USE OF, OR RELIANCE UPON THIS DRAWING BY ANY THIRD PARTY. THIS DRAWING MAY HAVE DEFORMED FROM STATED SCALE DURING REPRODUCTION AND THEREFORE ANY SCALING SHOULD BE CARRIED OUT WITH CAUTION. THIS DRAWING SHALL ONLY BE USED FOR THE PURPOSES AGREED BY TERRAMARK LTD AND ITS CLIENT.

Client	
Southbase	
Address 29 Hamilton Street & 11 Oxford Street	
Legal Description Lots 9 & 10 DP 1219 & Lot 3 DP 391234	
Area 7683m ²	Record of Title 366119
Drawing Title Topographical Survey	
Date 03/02/2023	Scale (A3) 1:700
Client Ref. 230032	Drawing Reference 230032/1A

Legend:

- Post
- × Spot Height
- Tree
- Foul Sewer Manhole
- Stormwater Manhole
- Mudtank
- Water Manifold
- Fire Hydrant
- Power Pole
- Electricity Pillar
- Light Pole
- Edge of Seal Drive
- Edge of Seal Road
- Kerb
- Footpath
- Centre Line
- Fence
- Garden
- Hedge
- Building
- Top of Wall
- Bottom of Wall
- Contour Major
- Contour Minor
- Boundary
- - - Abbuttals
- - - Easement Boundary
- GDC GIS Stormwater
- GDC GIS Foul Sewer
- GDC GIS Water
- GPR Stormwater
- GPR Foul Sewer
- GPR Water
- GPR Electricity
- GPR Telecomms




- Notes:**
- 1) Horizontal Datum: North Taieri 2000
 - 2) Height Datum: NZVD2016
 - 3) Origin of Levels: LP I DP 12637 (F2D6) - Reduced Level: 72.28m
 - 4) Contour interval is:
Major - 0.5m
Minor - 0.1m
 - 5) Areas and dimensions are subject to verification upon survey.
 - 6) Easements, covenants and other legal instruments relating to this site may not be represented on this plan. A full investigation of legal records should be undertaken to confirm.
 - 7) Not all public & private drainage information has been shown on the plan.
 - 8) The position and alignment of services shown on this plan may have been obtained from Council records and are subject to the errors or omission of that data, they should not be used for design purposes. All services should be located on site before any design work is undertaken.
 - 9) Critical levels are to be checked and confirmed prior to design and construction.
 - 10) The contours shown on this plan have been electronically calculated between the survey fixed positions and may not represent the true ground levels.
 - 11) The size and positions of any trees shown on this plan is approximate and tree types should be confirmed by an arborist if critical.
 - 12) GPR measurements have been undertaken by KB Contractors. All water, foul sewer, and stormwater lines with a prefix of 'GPR' are based on measurements to these GPR markings and visible surface features. Cover to these services are based on the GPR information provided.
 - 13) Refer to plan 230032/1B for additional site topographical detail from 31/01/2023 & 15/02/2023.
 - 14) These notes are an intergral part of the plan.

DISCLAIMER:
THE CONCEPTS AND INFORMATION CONTAINED IN THIS DRAWING ARE THE COPYRIGHT OF TERRAMARK LTD. USE OR COPYING OF THIS DRAWING IN WHOLE OR PART WITHOUT WRITTEN PERMISSION OF TERRAMARK LTD CONSTITUTES AN INFRINGEMENT OF COPYRIGHT. TERRAMARK ACCEPTS NO LIABILITY OR RESPONSIBILITY WHATSOEVER FOR, OR IN RESPECT OF, ANY USE OF, OR RELIANCE UPON THIS DRAWING BY ANY THIRD PARTY. THIS DRAWING MAY HAVE DEFORMED FROM STATED SCALE DURING REPRODUCTION AND THEREFORE ANY SCALING SHOULD BE CARRIED OUT WITH CAUTION. THIS DRAWING SHALL ONLY BE USED FOR THE PURPOSES AGREED BY TERRAMARK LTD AND ITS CLIENT.

Client		Southbase	
Address		29 Hamilton Street & 11 Oxford Street	
Legal Description		Lots 9 & 10 DP 1219 & Lot 3 DP 391234	
Area	Record of Title	7683m ²	366119
Drawing Title		Topographical Survey	
Date	Scale (A3)	13/04/2023	1:600
Client Ref.	Drawing Reference.	230032	230032/2



LEGEND:
 PROPOSED
 73.0 CONTOUR - MAJOR 0.5m INTERVAL(m)
 73.2 CONTOUR - MINOR 0.1m INTERVAL (m)
 RETAINING WALL



**ISSUED FOR
 RESOURCE CONSENT**

0 RESOURCE CONSENT	WB 16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
Revision						



Project Title
**PACKAGE GORE
 29 HAMILTON STREET
 EAST GORE
 GORE**

Sheet Title
**FINISHED GROUND
 CONTOURS PLAN**

Level 1
 214 Durham Street South,
 Christchurch Central
 Christchurch 8011
 +64 3 374 6515
 calibregroup.com




Scale (A1 Original) 1:250	(A3) 1:500	
Project No	Sheet	Revision
713093.001	C200	0



EARTHWORKS NOTES

1. ALL EARTHWORKS IS TO BE COMPLETED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS AND THE LOCAL TERRITORIAL AUTHORITIES' CODES OF PRACTICE FOR LAND DEVELOPMENT.
2. THESE DRAWINGS DO NOT NECESSARILY SHOW ALL EXISTING SERVICES. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ACCURATELY LOCATE AND PROTECT EXISTING SERVICES BEFORE EXCAVATION AND TAKE ALL CARE TO PROTECT THEM DURING CONSTRUCTION. THE CONTRACTOR SHALL LIAISE WITH THE APPLICABLE SERVICE PROVIDERS BEFORE COMMENCING ANY WORK.
3. THE CONTRACTOR PROVIDE EROSION AND SEDIMENT CONTROL (ESC) MEASURES IN ACCORDANCE WITH THE PROJECT DRAWINGS SPECIFICATIONS AND REGIONAL COUNCIL (ES) GUIDELINES. ALL ESC MEASURES MUST BE OPERATIONAL PRIOR TO ANY OTHER WORKS COMMENCING ON SITE. THE CONTRACTOR HAS SOLE RESPONSIBILITY FOR ENSURING THAT ESC MEASURES ARE MAINTAINED AND EFFECTIVE AT ALL TIMES.
4. THE CONTRACTOR GRADE EARTHWORKS TO THE LEVELS SHOWN, HOWEVER, FINAL MARRYING IN AND SHAPING OF EARTHWORKS IS SUBJECT TO THE ENGINEER'S APPROVAL. EARTHWORKS ARE TO BE UNDERTAKEN AND COMPLETED WITHIN THE MINIMUM POSSIBLE TIME FRAME. ONCE EARTHWORKS ARE COMPLETED IN AN AREA AND FINAL LEVELS ARE REACHED, THE AREA SHALL BE STABILISED BY AN APPROVED METHOD AS SOON AS PRACTICABLE.
5. ALL EXCAVATIONS OF UNSUITABLE OR SATURATED MATERIALS ARE TO BE INSPECTED BY THE ENGINEER PRIOR TO FILLING.



CUT / FILL DEPTHS		
LOWER VALUE	UPPER VALUE	COLOUR
-1.0	to -0.8 m	Dark Red
-0.8	to -0.6 m	Red
-0.6	to -0.4 m	Dark Red
-0.4	to -0.2 m	Red
-0.2	to 0.0 m	Light Red
0.0	to 0.2 m	Light Green
0.2	to 0.4 m	Green
0.4	to 0.6 m	Dark Green
0.6	to 0.8 m	Very Dark Green
0.8	to 1.0 m	Black
1.0	to 1.2 m	Black
1.2	to 1.4 m	Black

CUT AND FILL VOLUMES		
VOLUME CUT (m³)	VOLUME FILL (m³)	NET (m³)
647	1,318	671

- NOTES:**
1. EARTHWORKS VOLUME ARE MEASURED FROM EXISTING SURFACE TO FINISHED GROUND SURFACE AND ARE APPROXIMATE ONLY. NO TOPSOIL OR SUBGRADE LEVELS HAVE BEEN CONSIDERED.

HAMILTON STREET

EXISTING R.O.W

ISSUED FOR RESOURCE CONSENT

0 RESOURCE CONSENT	WB 16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
Surveyed		TERRAMARK	13.04.2023	Client		
Designed		M.TAM	09.05.23	Project Title		
Drawn		M.TOLEDO	09.05.23	PACKAGE GORE		
Reviewed		B.HURRING	09.05.23	29 HAMILTON STREET		
App		W.BLANCHFIELD	09.05.23	EAST GORE		
				GORE		



Project Title
PACKAGE GORE
29 HAMILTON STREET
EAST GORE
GORE

Sheet Title
CUT AND FILL
DEPTH CONTOURS PLAN

Level 1
 214 Durham Street South,
 Christchurch Central
 Christchurch 8011
 +64 3 374 6515
 calibregroup.com



Scale (A1 Original)	1:250	(A3) 1:500
Project No	713093.001	Sheet
		C201
Revision		0

Verify all dimensions on site before commencing work. Prioritise figured dimensions over scaling. Refer all discrepancies to Calibre. This document and the copyright in this document remain the property of Calibre Consulting Limited. The contents of this document may not be reproduced either in whole or in part by any means whatsoever without the prior written consent of Calibre Consulting Limited.



- NOTES:**
- REFER SHEET C305 FOR ROAD AND KERB LONG SECTIONS.
 - REFER SHEET C400 SERIES FOR SERVICES PLAN.

- LEGEND**
- PROPOSED**
- PROPOSED BOUNDARY
 - KERB & CHANNEL
 - FINISHED FLOOR LEVEL
 - RETAINING WALL
 - BUILDING
 - VEHICLE AREA
 - PATH/ PATIO AREA
 - FOOTPATH
 - VEHICLE CROSSING
 - TIMBER DECK
 - LANDSCAPE AREA
 - BERM
- REFER ARCHITECTURAL PLANS FOR PAVEMENT FINISH TYPE**



ISSUED FOR RESOURCE CONSENT

0 RESOURCE CONSENT	WB 16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
<p>Verify all dimensions on site before commencing work. Prioritise figured dimensions over scaling. Refer all discrepancies to Calibre. This document and the copyright in this document remain the property of Calibre Consulting Limited. The contents of this document may not be reproduced either in whole or in part by any means whatsoever without the prior written consent of Calibre Consulting Limited.</p>						




Project Title
 PACKAGE GORE
 29 HAMILTON STREET
 EAST GORE
 GORE

Sheet Title
 PAVEMENT PLAN


Level 1
 214 Durham Street South,
 Christchurch Central
 Christchurch 8011
 +64 3 374 6515
 calibregroup.com




Scale (A1 Original) 1:250	(A3) 1:500	
Project No	Sheet	Revision
713093.001	C300	0



VESTED ROAD TYPICAL SECTION A
 1:25 @ A1
 1:50 @ A3
 C300



RIGHT OF WAY TYPICAL SECTION B
 1:50 @ A1
 1:100 @ A3
 C300



EXISTING RIGHT OF WAY TYPICAL SECTION C
 1:25 @ A1
 1:50 @ A3
 C300

**ISSUED FOR
 RESOURCE CONSENT**

0 RESOURCE CONSENT Revision	WB	16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
	WB	16.05.23	Reviewed	B.HURRING	09.05.23		
	WB	16.05.23	Drawn	M.TOLEDO	09.05.23		
	WB	16.05.23	Designed	M.TAM	09.05.23		
	WB	16.05.23	Surveyed	TERRAMARK	13.04.2023		




Project Title
 PACKAGE GORE
 29 HAMILTON STREET
 EAST GORE
 GORE

Sheet Title
 ROAD TYPICAL SECTIONS

Level 1
 214 Durham Street South,
 Christchurch Central
 Christchurch 8011
 +64 3 374 6515
 calibregroup.com



Scale (A1 Original)		
SCALE AS NOTED		
Project No	Sheet	Revision
713093.001	C310	0



NOTES:
1. REFER INDIVIDUAL SERVICE PLAN FOR NOTES.

LEGEND

EXISTING


- SW STORMWATER
- ⊕ STORMWATER MH
- ⊕ SUMP (SINGLE)
- WW WASTEWATER
- ⊕ WASTEWATER MH
- W WATER
- ⊕ WATER VALVE
- P POWER
- ⊕ POWER PILLAR
- ⊕ POWER POLE
- ⊕ LIGHT POLE
- T TELECOM

PROPOSED

- SW STORMWATER
- STORMWATER LATERALS
- STORMWATER FLOW DIRECTION
- ⊕ STORMWATER MH
- ⊕ SINGLE SUMP
- WW WASTEWATER
- WASTEWATER LATERALS
- WASTEWATER FLOW DIRECTION
- ⊕ WASTEWATER MH
- WM WATERMAIN
- W RIDER MAIN
- WATER LATERALS
- ⊕ FIRE HYDRANT
- ⊕ WATER METER
- ⊕ WATER VALVE

SYMBOLS

- ▭ BUILDING
- ▭ VEHICLE AREA
- ▭ PATH/ PATIO AREA
- ▭ FOOTPATH
- ▭ VEHICLE CROSSING
- ▭ TIMBER DECK
- ▭ BERM



**ISSUED FOR
RESOURCE CONSENT**

0 RESOURCE CONSENT	WB 16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
<p>Verify all dimensions on site before commencing work. Prioritise figured dimensions over scaling. Refer all discrepancies to Calibre. This document and the copyright in this document remain the property of Calibre Consulting Limited. The contents of this document may not be reproduced either in whole or in part by any means whatsoever without the prior written consent of Calibre Consulting Limited.</p>						




Project Title
**PACKAGE GORE
29 HAMILTON STREET
EAST GORE
GORE**

Sheet Title
COMBINED SERVICES PLAN

Level 1
214 Durham Street South,
Christchurch Central
Christchurch 8011
+64 3 374 6515
calibregroup.com



Scale (A1 Original) 1:250	(A3) 1:500	
Project No	Sheet	Revision
713093.001	C400	0



- DRAINAGE NOTES**
1. ALL DRAINAGE WORKS TO BE IN ACCORDANCE WITH NZBC E1/AS1: SURFACE WATER AND G13/AS2 FOUL WATER AND CSS 2019 PART 3.
 2. STORMWATER INFRASTRUCTURE TO BE LAID AND INSTALLED IN TERMS OF THE APPROVED BUILDING CONSENT.
 3. ALL CONNECTIONS TO COUNCIL DRAINS AND WATERWAYS MUST BE CARRIED OUT BY A COUNCIL AUTHORISED DRAIN LAYER, A LIST OF WHOM IS AVAILABLE ON THE COUNCIL WEBSITE.
 4. CONTRACTOR IS TO PROVIDE AS-BUILT RECORDS OF ALL BURIED SERVICES TO THE ENGINEER & COUNCIL OFFICERS.
 5. PIPE MATERIALS SHALL BE:
 - DN 100 uPVC SN16 TO AS/NZS1260
 - DN 150 uPVC SN16 TO AS/NZS1260
 6. ALL PIPES LAID AT A MINIMUM GRADE OF 1:120 OR GREATER UNLESS STATED OTHERWISE.
 7. ALL LATERALS DN100 UNLESS STATED OTHERWISE.
 8. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR ENSURING ALL INSPECTIONS AND APPROVALS REQUIRED BY THE BUILDING CONSENT ARE COMPLETED.
 9. THE CONTRACTOR IS TO NOTIFY THE COUNCIL INSPECTORS 48HRS BEFORE ANY PIPES ARE BACKFILLED FOR INSPECTION.
 10. ALL SUMP LEADS ARE TO BE DN225 uPVC SN8 UNLESS STATED OTHERWISE.

- NOTES FOR DRAINAGE WORK CARRIED OUT IN THE LEGAL ROADWAY OR ON COUNCIL OWNED LAND.**
1. ALL DRAINAGE WORKS WITHIN THE LEGAL ROADWAY OR ON COUNCIL OWNED LAND ARE TO BE CARRIED OUT IN ACCORDANCE WITH CHRISTCHURCH CITY COUNCILS CSS SPECIFICATION 2019 PARTS 1-7 AND INFRASTRUCTURE DESIGN STANDARD (IDS).
 2. ONLY AUTHORISED DRAIN LAYERS SHALL BE PERMITTED TO CARRY OUT WASTEWATER AND STORMWATER RETICULATION WORK WHERE IT CONNECTS INTO COUNCIL RETICULATION OR WHERE INFRASTRUCTURE IS GOING TO BE VESTED IN COUNCIL OWNERSHIP.
 3. ALL DRAINAGE PIPES TO BE uPVC UNLESS STATED OTHERWISE ON THE PLAN.
 4. ALL uPVC DN100, DN150 AND DN175 DRAINAGE PIPES TO HAVE A MINIMUM PIPE CLASS OF SN16.
 5. ALL uPVC DN225 DRAINAGE PIPES AND GREATER ARE TO HAVE A MINIMUM PIPE CLASS OF SN8.
 6. ALL uPVC PIPES TO HAVE A MINIMUM COVER AS PER NZBC - G13 AND E1.
 7. ALL PIPE HAUNCHING AND BACKFILLING TO COMPLY WITH CCC CSS SPECIFICATIONS.

- LEGEND EXISTING**
- SW - STORMWATER
 - SWMH - STORMWATER MH
 - SUMP (SINGLE)
 - WW - WASTEWATER
 - WWMH - WASTEWATER MH
 - W - WATER
 - WV - WATER VALVE
 - P - POWER
 - PP - POWER PILLAR
 - PP - POWER POLE
 - LP - LIGHT POLE
 - T - TELECOM

- PROPOSED**
- SW - STORMWATER
 - SWL - STORMWATER LATERALS
 - SWFD - STORMWATER FLOW DIRECTION
 - SWMH - STORMWATER MH
 - SUMP - SINGLE SUMP
 - OFD - OVERLAND FLOWPATH DIRECTION
 - WW - WASTEWATER
 - WWD - WASTEWATER FLOW DIRECTION
 - WWMH - WASTEWATER MH
 - WM - WATERMAIN
 - W - RIDER MAIN
 - FH - FIRE HYDRANT
 - WM - WATER METER
 - WV - WATER VALVE
 - B - BUILDING
 - VA - VEHICLE AREA
 - PPA - PATH/ PATIO AREA
 - F - FOOTPATH
 - VC - VEHICLE CROSSING
 - TD - TIMBER DECK
 - B - BERM



ISSUED FOR RESOURCE CONSENT

0 RESOURCE CONSENT	WB 16.05.23	App Date	Approved	W.BLANCHFIELD	09.05.23
1	13.04.2023	Client	TERRAMARK	13.04.2023	Surveyed
2	09.05.23	Designed	M.TAM	09.05.23	
3	09.05.23	Drawn	M.TOLEDO	09.05.23	
4	09.05.23	Reviewed	B.HURRING	09.05.23	



Project Title
PACKAGE GORE
29 HAMILTON STREET
EAST GORE
GORE


Sheet Title
STORMWATER PLAN

Level 1
214 Durham Street South,
Christchurch Central
Christchurch 8011
+64 3 374 6515
calibregroup.com



Scale (A1 Original)	1:250	(A3) 1:500
Project No	713093.001	Sheet
Revision	C401	0

Verify all dimensions on site before commencing work. Prioritise figured dimensions over scaling. Refer all discrepancies to Calibre. This document and the copyright in this document remain the property of Calibre Consulting Limited. The contents of this document may not be reproduced either in whole or in part by any means whatsoever without the prior written consent of Calibre Consulting Limited.



- DRAINAGE NOTES**
1. ALL DRAINAGE WORKS TO BE IN ACCORDANCE WITH NZBC E1/AS1: SURFACE WATER AND G13/AS2 FOUL WATER AND CSS 2019 PART 3.
 2. STORMWATER INFRASTRUCTURE TO BE LAID AND INSTALLED IN TERMS OF THE APPROVED BUILDING CONSENT.
 3. ALL CONNECTIONS TO COUNCIL DRAINS AND WATERWAYS MUST BE CARRIED OUT BY A COUNCIL AUTHORISED DRAINLAYER. A LIST OF WHOM IS AVAILABLE ON THE COUNCIL WEBSITE.
 4. CONTRACTOR IS TO PROVIDE AS-BUILT RECORDS OF ALL BURIED SERVICES TO THE ENGINEER & COUNCIL OFFICERS.
 5. PIPE MATERIALS SHALL BE:
 - DN 100 uPVC SN16 TO AS/NZS1260
 - DN 150 uPVC SN16 TO AS/NZS1260
 6. ALL PIPES LAID AT A MINIMUM GRADE OF 1:120 OR GREATER UNLESS STATED OTHERWISE.
 7. ALL LATERALS DN100 UNLESS STATED OTHERWISE.
 8. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR ENSURING ALL INSPECTIONS AND APPROVALS REQUIRED BY THE BUILDING CONSENT ARE COMPLETED.
 9. THE CONTRACTOR IS TO NOTIFY THE COUNCIL INSPECTORS 48HRS BEFORE ANY PIPES ARE BACKFILLED FOR INSPECTION.

- NOTES FOR DRAINAGE WORK CARRIED OUT IN THE LEGAL ROADWAY OR ON COUNCIL OWNED LAND.**
1. ALL DRAINAGE WORKS WITHIN THE LEGAL ROADWAY OR ON COUNCIL OWNED LAND ARE TO BE CARRIED OUT IN ACCORDANCE WITH CHRISTCHURCH CITY COUNCIL'S CSS SPECIFICATION 2019 PARTS 1-7 AND INFRASTRUCTURE DESIGN STANDARD (IDS).
 2. ONLY AUTHORISED DRAIN LAYERS SHALL BE PERMITTED TO CARRY OUT WASTEWATER AND STORMWATER RETICULATION WORK WHERE IT CONNECTS INTO COUNCIL RETICULATION OR WHERE INFRASTRUCTURE IS GOING TO BE VESTED IN COUNCIL OWNERSHIP.
 3. ALL DRAINAGE PIPES TO BE uPVC UNLESS STATED OTHERWISE ON THE PLAN.
 4. ALL uPVC DN100, DN150 AND DN175 DRAINAGE PIPES TO HAVE A MINIMUM PIPE CLASS OF SN16.
 5. ALL uPVC DN225 DRAINAGE PIPES AND GREATER ARE TO HAVE A MINIMUM PIPE CLASS OF SN8.
 6. ALL uPVC PIPES TO HAVE A MINIMUM COVER AS PER NZBC - G13 AND E1.
 7. ALL PIPE HAUNCHING AND BACKFILLING TO COMPLY WITH CCC CSS SPECIFICATIONS.

- LEGEND EXISTING**
- SW - STORMWATER
 - ⊕ - STORMWATER MH SUMP (SINGLE)
 - WW - WASTEWATER
 - ⊙ - WASTEWATER MH
 - W - WATER
 - ⊕ - WATER VALVE
 - P - POWER
 - ⊕ - POWER PILLAR
 - ⊕ - POWER POLE
 - ⊕ - LIGHT POLE
 - ⊕ - TELECOM

- PROPOSED**
- SW - STORMWATER
 - - STORMWATER FLOW DIRECTION
 - ⊕ - STORMWATER MH SUMP
 - ⊕ - SINGLE SUMP
 - WW - WASTEWATER
 - - WASTEWATER LATERALS
 - - WASTEWATER FLOW DIRECTION
 - ⊙ - WASTEWATER MH
 - WM - WATERMAIN
 - W - RIDER MAIN
 - ⊕ - FIRE HYDRANT
 - ⊕ - WATER METER
 - ⊕ - WATER VALVE
 - ▭ - BUILDING
 - ▭ - VEHICLE AREA
 - ▭ - PATH/ PATIO AREA
 - ▭ - FOOTPATH
 - ▭ - VEHICLE CROSSING
 - ▭ - TIMBER DECK
 - ▭ - BERM



ISSUED FOR RESOURCE CONSENT

0 RESOURCE CONSENT	WB 16.05.23	App Date	Approved	W.BLANCHFIELD	09.05.23
Revised					




Project Title
**PACKAGE GORE
29 HAMILTON STREET
EAST GORE
GORE**

Sheet Title
WASTEWATER PLAN

Level 1
214 Durham Street South,
Christchurch Central
Christchurch 8011
+64 3 374 6515
calibregroup.com



Scale (A1 Original)	1:250	(A3) 1:500
Project No	713093.001	Sheet C450
Revision		0



- WATER NOTES**
1. EACH LOT TO HAVE INDIVIDUAL OD25 MDPE SERVICE CONNECTIONS.
 2. PIPE MATERIALS TO BE OD25 MDPE PN12.5 TO AS/NZS 4130 UNLESS STATED OTHERWISE.
 3. VALVES POSITION INDICATIVE ONLY.

- LEGEND EXISTING**
- SW STORMWATER
 - ⊕ STORMWATER MH
 - ⊖ SUMP (SINGLE)
 - WW WASTEWATER
 - ⊕ WASTEWATER MH
 - W WATER
 - ⊕ WATER VALVE
 - P POWER
 - ⊕ POWER PILLAR
 - ⊕ POWER POLE
 - ⊕ LIGHT POLE
 - T TELECOM

- PROPOSED**
- SW STORMWATER
 - STORMWATER FLOW DIRECTION
 - ⊕ STORMWATER MH
 - ⊖ SINGLE SUMP
 - WW WASTEWATER
 - WASTEWATER FLOW DIRECTION
 - ⊕ WASTEWATER MH
 - WM WATERMAIN
 - W RIDER MAIN
 - WATER LATERAL
 - ⊕ FIRE HYDRANT
 - ⊕ WATER METER
 - ⊕ WATER VALVE
- BUILDING
 VEHICLE AREA
 PATH/ PATIO AREA
 FOOTPATH
 VEHICLE CROSSING
 TIMBER DECK
 BERM



**ISSUED FOR
RESOURCE CONSENT**

0 RESOURCE CONSENT	WB 16.05.23	App	Date	Approved	W.BLANCHFIELD	09.05.23
Surveyed TERRAMARK 13.04.2023 Designed M.TAM 09.05.23 Drawn M.TOLED0 09.05.23 Reviewed B.HURRING 09.05.23 Approved W.BLANCHFIELD 09.05.23						



Project Title
**PACKAGE GORE
29 HAMILTON STREET
EAST GORE
GORE**

Sheet Title
WATER SUPPLY PLAN

Level 1
214 Durham Street South,
Christchurch Central
Christchurch 8011
+64 3 374 6515
calibregroup.com



Scale (A1 Original) 1:250	(A3) 1:500	
Project No	Sheet	Revision
713093.001	C500	0

Appendix B Stormwater Calculations

Pre Development Flow - Internal Site Area

Project: KO - 29 Hamilton St, Gore
Job No. 713093.001

Date: 24/03/2023
Designed by: Michael Tam
Reviewed by: Brendan Hurring

Notes:

- Catchment is based on topographical survey "230032/1B" recieved from Terramark on 23/02/2023.
- The pre-development runoff discharges are based on historical rainfall intensity data from HIRDS.
- This runoff calculation sheet is for pre- and post-development flow discharge comparison purposes only, no

Rational Method as per NZBC E1 Surface Water

Rainfall = Historical Data from HIRDS
Average Slope = 0 - 2%
Storm Return Period = 10 Years

Time of Concentration Tc = 10 mins
Total Site Area A = 7685 m²

Surface Run Off

Surface:	Catchment Areas:	Runoff Coefficients:	Effective Areas:
Roof	A1= 868m ²	C1= 0.90	781m ²
Paved Areas	A2= 4106m ²	C2= 0.85	3490m ²
Berm / Garden	A3= 2711m ²	C3= 0.30	813m ²
Future Development Area	A4= 0m ²	C4= 0.65	0m ²
Permeable Pavement	A5= 0m ²	C5= 0.50	0m ²
Total Site Area:	7685m²	Total Effective Area:	5084m²

Rainfall Intensity Data:

Source : Historical Data from HIRDS

Units : mm/h

Duration (min) NB: in hours below								
Return Period Years	10min 0.2hr	20min 0.3hr	30min 0.5hr	60min 1.0hr	120min 2.0hr	360min 6.0hr	720min 12.0hr	1440min 24.0hr
2	29.5	20.2	16.1	10.9	7.3	3.7	2.4	1.6
5	42.8	28.9	22.8	15.2	10.0	5.0	3.2	2.0
10	54.2	36.2	28.4	18.7	12.2	6.0	3.8	2.4
20	67.4	44.6	34.8	22.7	14.6	7.2	4.5	2.8
50	88.3	57.7	44.8	28.8	18.4	8.8	5.5	3.4
100	107.0	69.4	53.6	34.1	21.6	10.2	6.3	3.8

Runoff Discharges:

Units : m³/h

	10min	20min	30min	60min	120min	360min	720min	1440min
2	150.0	102.7	81.9	55.4	36.9	19.0	12.4	8.0
5	217.6	146.9	115.9	77.3	50.7	25.5	16.4	10.4
10	275.6	184.1	144.4	95.1	62.0	30.7	19.5	12.3
20	342.7	226.8	176.9	115.4	74.2	36.4	22.9	14.2
50	449.0	293.4	227.8	146.4	93.6	44.7	27.8	17.1
100	544.0	352.9	272.5	173.4	109.8	51.9	31.9	19.5

Runoff Discharges:

Units : l/s

	10min	20min	30min	60min	120min	360min	720min	1440min
2	41.7	28.5	22.7	15.4	10.2	5.3	3.4	2.2
5	60.4	40.8	32.2	21.5	14.1	7.1	4.5	2.9
10	76.5	51.1	40.1	26.4	17.2	8.5	5.4	3.4
20	95.2	63.0	49.1	32.1	20.6	10.1	6.4	4.0
50	124.7	81.5	63.3	40.7	26.0	12.4	7.7	4.7
100	151.1	98.0	75.7	48.2	30.5	14.4	8.9	5.4

Runoff Volumes:

Units : m³

	10min	20min	30min	60min	120min	360min	720min	1440min
2	25.0	34.2	40.9	55.4	73.7	114.1	148.3	191.6
5	36.3	49.0	58.0	77.3	101.4	153.1	196.5	248.9
10	45.9	61.4	72.2	95.1	124.1	184.3	234.3	294.1
20	57.1	75.6	88.5	115.4	148.5	218.4	274.6	341.7
50	74.8	97.8	113.9	146.4	187.1	268.5	333.7	410.0
100	90.7	117.6	136.3	173.4	219.6	311.2	383.2	467.4

Post Development Flow - Internal Site Area

Project: KO - 29 Hamilton St, Gore
Job No. 713093.001

Date: 24/03/2023
Designed by: Michael Tam
Reviewed by: Brendan Hurring

Notes:

- Catchment is based on architectural plan "Z1201-9" received from Ignite Architects on 16/03/2023.
- The post-development runoff discharges are based on RCP8.5 climate factor for the period 2081-2100 rainfall intensity data from HIRDS.
- This runoff calculation sheet is for pre- and post-development flow discharge comparison purposes only, no upstream catchment is considered.

Rational Method as per NZBC E1 Surface Water

Rainfall = RCP8.5 for the period 2081-2100 from HIRDS
Average Slope = 0 - 2%
Storm Return Period = 10 Years

Time of Concentration Tc = 10 mins
Total Site Area A = 7685 m²

Surface Run Off

Surface:	Catchment Areas:	Runoff Coefficients:	Effective Areas:
Roof	A1= 1284m ²	C1= 0.90	1156m ²
Semi-Permeable Pavers	A2= 795m ²	C2= 0.85	676m ²
Road / Driveway	A7= 2063m ²	C7= 0.85	1753m ²
Footpath	A6= 502m ²	C6= 0.85	426m ²
Berm / Garden	A3= 3042m ²	C3= 0.30	913m ²
Future Development Area	A4= 0m ²	C4= 0.65	0m ²
Total Site Area:	7685m²	Total Effective Area:	3585m²

Rainfall Intensity Data:

Source : RCP8.5 for the period 2081-2100 from HIRDS

Units : mm/h

Duration (min) NB: in hours below	10min	20min	30min	60min	120min	360min	720min	1440min
Return Period Years	0.2hr	0.3hr	0.5hr	1.0hr	2.0hr	6.0hr	12.0hr	24.0hr
2	38.8	26.6	21.2	14.3	9.4	4.7	3.0	1.9
5	57.0	38.4	30.4	20.2	13.1	6.4	4.0	2.5
10	72.5	48.4	38.1	25.0	16.1	7.7	4.8	2.9
20	90.5	59.9	46.8	30.5	19.5	9.2	5.6	3.4
50	119.0	77.8	60.4	38.8	24.5	11.4	6.9	4.1
100	145.0	93.7	72.3	46.1	28.8	13.2	7.9	4.7

Runoff Discharges:

Units : m³/h

Duration (min)	10min	20min	30min	60min	120min	360min	720min	1440min
2	139.1	95.4	76.0	51.3	33.8	16.8	10.6	6.7
5	204.3	137.7	109.0	72.4	47.0	22.9	14.3	8.8
10	259.9	173.5	136.6	89.6	57.7	27.7	17.1	10.4
20	324.4	214.7	167.8	109.3	69.9	33.0	20.2	12.2
50	426.6	278.9	216.5	139.1	87.8	40.9	24.6	14.7
100	519.8	335.9	259.2	165.3	103.2	47.3	28.4	16.7

Runoff Discharges:

Units : l/s

Duration (min)	10min	20min	30min	60min	120min	360min	720min	1440min
2	38.6	26.5	21.1	14.2	9.4	4.7	3.0	1.9
5	56.8	38.2	30.3	20.1	13.0	6.4	4.0	2.4
10	72.2	48.2	37.9	24.9	16.0	7.7	4.8	2.9
20	90.1	59.6	46.6	30.4	19.4	9.2	5.6	3.4
50	118.5	77.5	60.1	38.6	24.4	11.4	6.8	4.1
100	144.4	93.3	72.0	45.9	28.7	13.1	7.9	4.7

Runoff Volumes:

Units : m³

Duration (min)	10min	20min	30min	60min	120min	360min	720min	1440min
2	23.2	31.8	38.0	51.3	67.6	100.7	127.8	160.0
5	34.1	45.9	54.5	72.4	93.9	137.2	171.2	211.6
10	43.3	57.8	68.3	89.6	115.4	166.3	205.6	250.4
20	54.1	71.6	83.9	109.3	139.8	198.1	242.2	291.7
50	71.1	93.0	108.3	139.1	175.7	245.2	295.5	351.9
100	86.6	112.0	129.6	165.3	206.5	283.9	340.3	401.8

Pre- and Post-development Stormwater Calculations Summary

Project: KO - 29 Hamilton St, Gore
Job No. 713093.001

Date: 24/03/2023
Designed by: Michael Tam
Reviewed by: Brendan Hurring

Summary for Q10 Storm Event	Pre-development	Post-development	Post-development
Rainfall data	Historical data from HIRDS	Historical data from HIRDS	RCP8.5 for the period 2081-2100 from HIRDS
Q10 runoff discharge (l/s)	76.5	49.8	72.2
Q10 runoff volume (m ³)	45.9	29.9	43.3
Runoff discharge changes in % compared to pre-development	N/A	-34.9	-5.7
Runoff volume changes in % compared to pre-development	N/A	-34.9	-5.7
Is post-dev runoff < pre-dev runoff?	N/A	Yes	Yes

Summary for Q100 Storm Event	Pre-development	Post-development	Post-development
Rainfall data	Historical data from HIRDS	Historical data from HIRDS	RCP8.5 for the period 2081-2100 from HIRDS
Q100 runoff discharge (l/s)	151.1	98.4	144.4
Q100 runoff volume (m ³)	90.7	59.0	86.6
Runoff discharge changes in % compared to pre-development	N/A	-34.9	-4.5
Runoff volume changes in % compared to pre-development	N/A	-34.9	-4.5
Is post-dev runoff < pre-dev runoff?	N/A	Yes	Yes

Appendix C WSP Capacity Confirmation Email

Michael Tam

From: Carmen Knobloch <Carmen.Knobloch@kaingaora.govt.nz>
Sent: Wednesday, April 26, 2023 1:58 PM
To: Michael Tam
Subject: FW: Review email for Matt Bayliss - GDC - Preliminary results and ask if they want to run an option for 29 Hamilton street
Attachments: image004.wmz; image012.wmz

CAUTION: This email originated from outside of the organisation. Do not click links or open attachments unless you can verify that the content is safe, even it appears to come from someone you know.



Carmen Knobloch

Programme Manager
Programme Delivery Team 5
Construction and Innovation

Mobile: 021 240 6896
Email: carmen.knobloch@kaingaora.govt.nz

Freephone: 0800 801 601 | Kāinga Ora - Homes and Communities
PO BOX 2628 Wellington 6140 | New Zealand Government | www.kaingaora.govt.nz

From: Matt Bayliss <MBayliss@goredc.govt.nz>
Sent: Wednesday, 26 April 2023 1:51 PM
To: Foglia, Marion <Marion.Foglia@wsp.com>
Cc: Ripley, David <david.ripley@wsp.com>; Carmen Knobloch <Carmen.Knobloch@kaingaora.govt.nz>; PJ Alberts <PJ.Alberts@kaingaora.govt.nz>
Subject: RE: Review email for Matt Bayliss - GDC - Preliminary results and ask if they want to run an option for 29 Hamilton street

CAUTION: External email. Do not click or open attachments unless you recognise the sender and know the content is safe. If unsure use the Report Phishing button.

Hi Marion,

Thanks for the update.

Comments as follows:

- Water supply - a 0.2 m pressure drop is obviously pretty low and I think that would be acceptable.
- Wastewater – the key thing to understand is what the volume and percentage increase in overflows is occurring at the various overflow points
- Stormwater – you mention at the bottom of your email that you are looking for direction as to need look at solutions for Stormwater and Wastewater, however I also note that you are saying there is no increase in SW flooding from the development – are you suggesting some form of stormwater attenuation could be used to offset the increase in wastewater overflows? FYI any direction around consideration of solutions would need to come from KO – from my point of view I think it would be best to get a draft report of the results before starting to look at any solutions.

Thanks

Matt Bayliss | 3 Waters Asset Manager

T: 03 209 0330 | **DDI:** 03 209 0382 | **M:** 027 405 8411

E: mbayliss@goredc.govt.nz | **W:** www.goredc.govt.nz

Gore District Council, 29 Bowler Avenue, PO Box 8, Gore, 9740



Disclaimer

The information contained in this communication from Gore District Council is confidential. It is intended solely for use by the recipient and others authorized to receive it. If you are not the recipient, you are hereby notified that any disclosure, copying, distribution or taking action in relation of the contents of this information is strictly prohibited and may be unlawful.

From: Foglia, Marion <Marion.Foglia@wsp.com>

Sent: Wednesday, 26 April 2023 1:26 PM


To: Matt Bayliss <MBayliss@goredc.govt.nz>

Cc: Carmen Knobloch <Carmen.Knobloch@kaingaora.govt.nz>; PJ Alberts <PJ.Alberts@kaingaora.govt.nz>; Ripley, David <david.ripley@wsp.com>


Subject: FW: Review email for Matt Bayliss - GDC - Preliminary results and ask if they want to run an option for 29 Hamilton street

Hi Matt,

I am contacting you about the 3 waters modelling project in 29 Hamilton Street development conducting by Kainga Ora for GDC.



Longitudinal profile along the wastewater network for a 5 yr ARI event



- For the stormwater network, a stormwater catchment is covering the full development area + the surrounded field as set into the base model.
 - o For the stormwater network there is slight increase into the total volume and flow but there is no increase into the flood depth. As shown in the screenshot below the difference between the base and development model is showing a very small blue light area (less than 2cm).

Flood map with the 29 Hamilton Street development – 5 yr ARI

New development



Difference in the flood map between base and development scenario during a 5yr ARI event.



To this point:

The water supply assessment will be carry on and deliver more detailed during the week.

The wastewater and stormwater assessment with the 5yr ARI event shows overflow and flooding issues.

However, those issue are observed in the base model (without the 29 Hamilton Street development). The additional development triggers an increase into the volume and flow within the wastewater network but the increase is not significant.

The expecting flood is showing no depth differences between the base and the development scenario.

From those preliminary results we would appreciate to have the income from GDC either or not to carry on with an option for the wastewater and stormwater to accommodate the development. I am happy to have a call if you want to discuss further about the results.

Thank you



Marion Foglia
Engineer – Water

M: +64 21 955 239
Marion.Foglia@wsp.com
wsp.com/nz

NOTICE: This communication and any attachments ("this message") may contain information which is privileged, confidential, proprietary or otherwise subject to restricted disclosure under applicable law. This message is for the sole use of the intended recipient(s). Any unauthorized use, disclosure, viewing, copying, alteration, dissemination or distribution of, or reliance on, this message is strictly prohibited. If you have received this message in error, or you are not an authorized or intended recipient, please notify the sender immediately by replying to this message, delete this message and all copies from your e-mail system and destroy any printed copies.

-LAEmHhHzdJzBITWfa4Hgs7pbKl

www.govt.nz - your guide to finding and using New Zealand government services

Any opinions expressed in this message are not necessarily those of Kāinga Ora. This message and any files transmitted with it are confidential, may be legally privileged, and are solely for the use of the intended recipient. If you are not the intended recipient or the person responsible for delivery to the intended recipient, you have received this message in error.

Please:

- (1) reply promptly to that effect, and remove this email, any attachment and the reply from your system;
- (2) do not use, disclose or act on this email in any other way. Thank you.

Appendix D Floor Level and Attenuation Correspondence

Table 1: Record of key discussions and outcomes with respect to stormwater management and mitigation.

20/02/2023	Email	<p>GDC - M. Bayliss Confirmed dispensation for the 3000l tank requirement can be granted if the attenuation / soakage is greater than the pre-development flows. Confirmed first flush treatment is required. Onsite soakage is acceptable to provide treatment and attenuation of flows at the same time. Confirmed the development can discharge to the existing stormwater network on Hamilton Street as long as the post development flows do not exceed the pre-development flows. Preference would still be to have some form of attenuation incorporated into the treatment component even the post-development peak flow is less than the pre-development peak flow.</p>
27/02/2023	Email	<p>GDC - M. Bayliss Further confirmed some other forms of attenuation were still required even if the dispensation on the rainwater tanks were granted. Suggested to refer to Bylaw section 4.3.7 for guidance on the need to incorporate green infrastructure. Suggested a soakage / attenuation system that provided a capacity to take the first 72,000l of a rainfall event (24 proposed units x 3000l of rainwater storage) might meet both the rainwater tank and green infrastructure requirements. Suggested if the attenuation / soakage system was going to be entirely for the development, vested in Council ownership was not encouraged.</p>
15/03/2023	Design team meeting	<p>Calibre - W. Blanchfield Recommended the attenuation basin to be located at the downstream end of the catchment, which is the frontage of the development with Hamilton Street. This would work the best for secondary flow path. Flow needs to be directed into Hamilton Street as Kainga Ora do not have the right to drain water through to Oxford Street Suggested to obtain dispensation from GDC about the requirement of having the 3000l rainwater tank for each new dwelling. Suggested to confirm with GDC regarding stormwater attenuation and treatment requirements.</p> <p>Kainga Ora - PJ. Albert Changing layout is not an option at this point. Vesting of soakage is not needed. It can be incorporated into landscape</p>
22/03/2023	Meeting	<p>GDC - M. Bayliss Would consider dispensation for the 3,000l tank requirement, but suggested to include attenuation into the design via green infrastructure.</p>

		<p>Would not intend the pond being vested in Council ownership.</p> <p>Rainfall intensity for the development can be taken from High Intensity Rainfall Design System (HIRDS)</p> <p>Rational method formula from the Building Code E1 can be used to work out the peak runoff</p>
29/03/2023	Email	<p>Calibre - W. Blanchfield</p> <p>A letter with supporting calculations, seeking a dispensation for the stormwater attenuation and acceptance of treatment methodology, had been submitted to Matt Bayliss from GDC.</p>
05/04/2023	Email	<p>GDC - M. Bayliss</p> <p>The primary function of the 3,000l rainwater tanks was to allow capture and reuse of rainwater, not for stormwater attenuation. If there is no intention to reuse for rainwater stored onsite, the 3,000l tank was still required for attenuation.</p> <p>The site required post-development flows to be less than the pre-development flows excluding any benefit gained from having the 3,000l rainwater tanks.</p> <p>The critical storm event the GDC downstream network was the 60-minute 20% AEP.</p> <p>Climate change needs to be taken into consideration.</p> <p>Confirmed that the Hynds Downstream Defender, First Defence High Capacity System or Stormwater 360 Cascade Separator designed to treat the first 25mm of rainfall or rainfall intensity of 5mm/hr would be acceptable for this development.</p>
06/04/2023	Pre-application meeting	<p>Calibre - B. Hurring</p> <p>Stated that no attenuation should not be required as calculations were provided to GDC in the dispensation application that the proposed development would generate less runoff than the pre-development situation.</p> <p>Commented if the 3000l tanks were for rainwater re-use, it could not be for attenuation which required releasing stormwater slowly instead of storing it. It could not be functional as rainwater re-use and stormwater attenuation at the same time as they contradict.</p> <p>GDC - M. Bayliss</p> <p>Would re-consider if the tanks were still required for attenuation.</p>
13/04/2023	Email	<p>Calibre- M. Tam</p> <p>The only option to attenuate stormwater based on the latest scheme was using tanks, subject to GDC final decision on whether attenuation is required.</p> <p>Each building would need to have approximately 1.8m³ of tank based on the last response from GDC.</p>
17/04/2023	Email	<p>Southbase - M. Gibowicz</p> <p>Asked if the removal of landscape in the middle of the cul-de-sac would cause a impact on the attenuation requirements.</p>

		<p>Calibre - M. Tam Confirmed the removal of landscape in the middle of the cul-de-sac would not cause a significant issue to the attenuation requirement, but would contribute to slight increase in required attenuation volume.</p>
26/04/2023	Email	<p>Matt Bayliss – GDC Confirmed that treatment of the hardstand area in the vested road and RoW will be sufficient.</p>
27/04/2023	Email	<p>GDC - Matt Bayliss <u>Option 1: Attenuation using tanks</u> Preference would be to have the tank size based on the roof size of each building. Low flow out to be sized to fill the tank during the 60-minute critical event. Low flow to be 200mm above the bottom of the tank to prevent debris blocking. High flow out to be sized to have a capacity for the 5-year 10-minute storm.</p> <p><u>Option 2: Attenuation using piped system</u> More preferable by GDC. The low flow outlet needs to be sized to ensure the attenuation fills up in a 5-year 60-minute storm. GDC predicts hydraulic grade of pipes in Hamilton St to be above ground level immediately outside the development during a 5-year 60-minute storm event.</p>

Table 2: Record of key discussions and outcomes with respect to minimum FFL

Date	Communications	Comments
25/01/2023	Email	<p>ES - G. Gilder ES was not enforcing any level changes but could provide a recommendation. Recommended to raise the site above the adjacent roads. Flood modelling was being prepared on behalf of ES with results due in May. This would address any potential improvements / upgrades to the flood protections, stopbanks etc.</p>
08/02/2023	Email	<p>ES - G. Gilder</p>

		<p>A minimum FFL of 73.75m NZVD 2016 would be required based on the low point at the intersection of Railway Esplanade and Hamilton Street.</p> <p>A minimum FFL of 74.25m NZVD 2016 would be required to allow for 0.2m depth of water flowing over tipping level and 0.3m of freeboard for wave effects from vehicles driving through the flood water.</p> <p>The minimum FFL of 74.25m NZVD 2016 was deemed to be impractical for the site.</p>
13/02/2023	Email	<p>GDC - M. Bayliss</p> <p>Suggested a minimum FFL of 73.3 NZVD 2016, approximately 300mm above the current ground level for most of the site.</p> <p>Deferred to ES to define the minimum FFL.</p>
20/02/2023	Design team meeting	<p>Kainga Ora - PJ Albers</p> <p>Verbally requested the minimum FFL for the development to be designed for a 200-year event</p> <p>General</p> <p>Contact Matt Bayliss for any 3-water queries</p>
22/02/2023	Email	<p>Kainga Ora - PJ Albers</p> <p>Requested comments from Calibre on the flood risk around the FFL's based on the current design taking into consideration that mitigation would be introduced and the current hardstand against permeable areas in the proposed design.</p> <p>Calibre - M. Sawirs</p> <p>Summarised the comments and recommendations provided by ES:</p> <ul style="list-style-type: none"> • The stopbank could only manage up to 70-year event. • The system was controlled by the low point at the intersection of Hamilton Street, and Railway Esplanade at RL73.50m NZVD 2016 (not from survey). • The minimum FFL of 73.75m suggested by ES was 250mm above the level of the low point, and 74.25m was 750mm above the low point (NZVD 2016). The FFL of 73.75m would be 1.25m above the crown of the road, and the FFL of 74.25m would be 1.75m above the crown of the road. <p>Designing the floor levels considering this stopbank being failure would need to be above RL 75.0m NZVD 2016.</p> <p>Commented conservative approach with respect to flooding, increasing the heights any further may displace too much water onto adjacent lots.</p> <p>Commented conservative approach with respect to value engineering, increasing the heights any further becomes very costly.</p>
22/03/2023	Email	<p>GDC - M. Bayliss</p> <p>Sent the previous pre-application meeting notes (25/01/2023) to Calibre and Southbase.</p>

		<p>The pre-application meeting notes:</p> <ul style="list-style-type: none"> • Included a picture that showed most of the site areas were not flooded for a 100-year event • Suggested a minimum FFL of 73.3m (300mm above the current ground level for most of the site) • Deferred to ES in terms of natural hazard flooding
06/04/2023	Pre-application meeting	<p>ES - G. Glider Advised that there would be a flood modelling due in May 2023, which would potentially be beneficial for defining the minimum FFL. Advised that there would be an upgrade to the existing stopbank which would be designed to have a 100-year flood protection.</p> <p>GDC - M. Bayliss Advised that the 100-year flood level provided by GDC was purely based on their internal infrastructure.</p>
11/04/2023	Email	<p>GDC - M. Bayliss Confirmed the 100-year flood level in the area of 29 Hamilton Street is 73.0m.</p> <p>Advised that Bylaw required 600mm freeboard from the 100-year flood level for any habitable dwellings. However, dispensation can be considered if a request and justification was provided.</p> <p>Calibre - W. Blanchfield Asked if KO would accept the development to be designed for a 100-year event only.</p> <p>Kainga Ora - C. Knobloch KO would prefer to work towards a 200-year event.</p>
17/04/2023	Email	<p>ES - G. Gilder Asked what datum GDC was based on. The heights suggested by ES were in terms of NZVD 2016. Commented ES did not have a firm opinion on a minimum floor level as it might be that the appropriate mitigation was impractical. ES did not have the 200-year flood level.</p>
18/04/2023	Email	<p>Calibre - M. Tam Recommended to retain the existing design FFL 73.75m in terms of NZVD 2016 subject to confirmation from GDC regarding their datum and if the 100-year flood level provided allowed for climate change factor.</p> <p>GDC - M. Bayliss Confirmed the 100-year flood level is 73.0m in terms of NZVD 2016.</p>

		<p>Confirmed GDC have not had any information regarding the 200-year flood level.</p> <p>Questioned the value in trying to design for a 200-year storm event.</p>
04/05/2023	Email	<p>Property Group - J. Skuse</p> <p>Confirmed that the 100-year flood level GDC had previous provided as 73.0m had not included an allowance for climate change.</p> <p>Stated “if climate change is going to make a substantial difference to this site it will also result in flooding of a large area of the surrounding land – when/if the Council upgraded the stormwater network in this area of town an allowance for climate change will be included – based on this, a minimum floor level of 73.60m would be acceptable.</p>
08/05/2023	Email	<p>WSP - M. Foglia</p> <p>Provided a 100-year flood map with climate change after construction of the development. It shows there are some flooding immediately outside of the development on Hamilton Street, and the 100-year flood level is 71.12m. There is minor flooding at the north-east corner of the development with a 100-year flood level of 73.42m</p> <p>Noted that the climate change is based on the outdated 2008 MfE guidance, not the latest 2018 guidance.</p>

Contact Us

Calibre Consulting Ltd
149025

Level 1, 214 Durham Street South, Christchurch Central,
Christchurch 8011
PO Box 13875, City East, Christchurch 8141
+64 3 374 6515